# NSN 5320-01-328-6106

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-328-6106



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.627 inches and 0.647 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.045 inches and 0.055 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.295 inches and 0.315 inches

### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

### Grip Length:

Between 0.307 inches and 0.317 inches

#### Thready Qty Per Inch (tpi):

32

### Thread Size:

0.190 inches

### Shear Strength:

95000 single pounds per square inch

#### **Special Features:**

Aluminum coating per hi-shear spec. 29-1

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

No

# NSN 5320-01-328-6106

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

