NSN 5320-01-328-7958

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-328-7958 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.253 inches and 1.273 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0801 inches **Shank Diameter:** Between 0.1630 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3306 inches and 0.3393 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** W/s: aircraft, b-2 bomber (atb) **Grip Length:** Between 0.933 inches and 0.943 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 96000 single pounds per square inch **Countersink Angle:** 130.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5320-01-328-7958

Pin-rivet - Page 2 of 2



Fiig:

A528u0