## NSN 5320-01-328-9251

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-328-9251



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.302 inches and 1.322 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.068 inches and 0.078 inches

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.475 inches and 0.605 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 0.807 inches and 0.817 inches

#### Thready Qty Per Inch (tpi):

24

## Thread Size:

0.312 inches

## Shear Strength:

95000 single pounds per square inch

#### **Special Features:**

Grit blast top of heads

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Thread Series Designator:

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-328-9251

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

