NSN 5320-01-329-1197

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-329-1197



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.878 inches and 0.898 inches

Head Style:

Err-090

Head Height:

Between 0.064 inches and 0.074 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.357 inches and 0.377 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.558 inches and 0.568 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

96000 single pounds per square inch

Special Features:

Grit blast top of heads

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-329-1197

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

