# NSN 5320-01-329-8233

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-329-8233

Head	C+1/	ın.
neau	OLV	<b>.</b>

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

### **Shank Diameter:**

Between 0.2580 inches and 0.2600 inches

### **Shank Style:**

Threaded self-plugging shank w/sleeve

### **Head Major Diameter:**

Between 0.499 inches and 0.507 inches

#### **Expansion Device:**

Threaded stem

#### **Grip Length:**

Between 0.907 inches and 0.969 inches

#### **Hardness Rating:**

30.0 rockwell c nut and 45.0 rockwell c nut

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Iron alloy 660

### **Material Specification:**

Ams 5732 assn standard single material response or ams 5737 assn standard single material response

### **Surface Treatment:**

**Passivate** 

### **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

### **Specification Data:**

80205-nas1672 professional/industrial association standard

### Shelf Life:

N/a

## **Unit Of Measure:**

#### **Demilitarization:**

No

### Fiig:

A040a0