# NSN 5320-01-329-8234

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-329-8234

Head	Ctvi	

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

#### **Shank Diameter:**

Between 0.1970 inches and 0.1990 inches

#### **Shank Style:**

Threaded self-plugging shank w/sleeve

#### **Head Major Diameter:**

Between 0.378 inches and 0.385 inches

#### **Expansion Device:**

Threaded stem

#### **Grip Length:**

Between 1.095 inches and 1.156 inches

#### **Hardness Rating:**

30.0 rockwell c nut and 45.0 rockwell c nut

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Iron alloy 660

## **Material Specification:**

Ams 5732 assn standard single material response or ams 5737 assn standard single material response

## **Surface Treatment:**

**Passivate** 

#### **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

## **Specification Data:**

80205-nas1672 professional/industrial association standard

## Shelf Life:

N/a

## **Unit Of Measure:**

## **Demilitarization:**

No

## Fiig:

A040a0