## NSN 5320-01-329-8236

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-329-8236



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.447 inches and 1.467 inches

#### Head Style:

Flush countersunk

### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

## Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.5018 inches and 0.5066 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

### Grip Length:

Between 1.057 inches and 1.067 inches

## Thready Qty Per Inch (tpi):

28

## **Thread Size:**

0.250 inches

#### Shear Strength:

95000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

## **Special Features:**

Crit blasted and furnished with o-ring

#### Material:

Titanium alloy uns r56400

## Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-329-8236

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

