

View Online at <https://aerobasegroup.com/nsn/5320-01-329-8237>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.8970 inches and 0.8975 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.064 inches and 0.074 inches

**Width Between Flats:**

Between 0.0791 inches and 0.0806 inches

**Shank Diameter:**

Between 0.1890 inches and 0.1895 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.357 inches and 0.377 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.5575 inches and 0.5675 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

96000 single pounds per square inch

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0