NSN 5320-01-330-8529

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-330-8529 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 0.815 inches and 0.835 inches **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.055 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style: Head Major Diameter:** Between 0.295 inches and 0.315 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.495 inches and 0.505 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Hi-kote 1 aluminum coating per hi-shear spec. 294 and cetyl alcohol lube per hi-shear spec. 305 Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5320-01-330-8529

Pin-rivet - Page 2 of 2



Fiig:

A528u0