NSN 5320-01-330-9885

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-330-9885 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.198 inches and 1.218 inches **Head Style:** Err-090 **Head Height:** Between 0.112 inches and 0.127 inches Width Between Flats: Between 0.2520 inches and 0.2555 inches **Shank Diameter:** 0.5601 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.829 inches and 0.864 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.433 inches and 0.443 inches Thready Qty Per Inch (tpi): 18 Minimum Yield Strength: 95000 pounds per square inch **Thread Size:** 0.5625 inches **Special Features:** Black dye on thd end Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Bms 10-85, cagec 81205 mfr ref single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

NSN 5320-01-330-9885

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0