## NSN 5320-01-331-1333

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-331-1333 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.135 inches and 1.155 inches **Head Style:** Err-090 **Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.745 inches and 0.755 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Grit blast top of heads Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-331-1333

Pin-rivet - Page 2 of 2



Fiig:

A528u0