NSN 5320-01-331-1335

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-331-1335 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.990 inches and 1.010 inches **Head Style:** Err-090 **Head Height:** Between 0.055 inches and 0.065 inches Width Between Flats: Between 0.0791 inches and 0.0801 inches **Shank Diameter:** Between 0.1635 inches and 0.1640 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.306 inches and 0.322 inches Lubrication: Solid film and cetyl alcohol **Grip Length:** Between 0.683 inches and 0.693 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.164 inches **Shear Strength:** 96000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-331-1335

Pin-rivet - Page 2 of 2



Fiig:

A528u0