# NSN 5320-01-331-7665

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-331-7665



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.690 inches and 0.710 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.045 inches and 0.055 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.295 inches and 0.315 inches

# Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 0.370 inches and 0.380 inches

#### Thready Qty Per Inch (tpi):

32

# Thread Size:

0.190 inches

# Shear Strength:

95000 single pounds per square inch

# **Special Features:**

Hi-kote 1, aluminum coating, spec. 294

# Material:

Titanium alloy uns r56400

# Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

# Thread Series Designator:

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-331-7665

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

