

View Online at <https://aerobasegroup.com/nsn/5320-01-332-3315>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

1.9765 inches

Head Style:

Err-090

Head Height:

Between 0.093 inches and 0.105 inches

Width Between Flats:

Between 0.1895 inches and 0.1930 inches

Shank Diameter:

Between 0.4360 inches and 0.4370 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.641 inches and 0.676 inches

Lubrication:

Cetyl alcohol

Grip Length:

1.4375 inches

Thready Qty Per Inch (tpi):

20

Thread Size:

0.4375 inches

Shear Strength:

108000 single pounds per square inch

Special Features:

32 micro inches on shank

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.