

View Online at <https://aerobasegroup.com/nsn/5320-01-332-3689>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.723 inches and 1.743 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.150 inches and 0.160 inches

**Width Between Flats:**

Between 0.1582 inches and 0.1617 inches

**Shank Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.565 inches and 0.600 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 1.183 inches and 1.198 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

201000 pounds per square inch

**Thread Size:**

0.375 inches

**Shear Strength:**

117000 single pounds per square inch

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Spec, 258, cagec 73197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0