## NSN 5320-01-332-3690

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-332-3690 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.847 inches and 1.867 inches **Head Style:** Err-090 **Head Height:** Between 0.150 inches and 0.160 inches Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.565 inches and 0.600 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.307 inches and 1.322 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 201000 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 117000 single pounds per square inch Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Spec, 258, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5320-01-332-3690

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0