

View Online at <https://aerobasegroup.com/nsn/5320-01-332-6575>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.944 inches and 0.964 inches

Head Style:

Err-090

Head Height:

Between 0.078 inches and 0.088 inches

Width Between Flats:

Between 0.1582 inches and 0.1617 inches

Shank Diameter:

Between 0.3735 inches and 0.3745 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.565 inches and 0.600 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.495 inches and 0.505 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Shear Strength:

108000 single pounds per square inch

Special Features:

32 micro inches on shank

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.