NSN 5320-01-332-6578

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-332-6578 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 2.030 inches **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.055 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style: Head Major Diameter:** Between 0.295 inches and 0.315 inches Lubrication: Cetyl alcohol **Grip Length:** 1.750 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 108000 single pounds per square inch **Special Features:** 32 micro inches on shank Material: Steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5320-01-332-6578

Pin-rivet - Page 2 of 2



	• -			
In	ıŧ	()t	Measure	•

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.