## NSN 5320-01-332-7353

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-332-7353

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.240 inches and 1.260 inches
Head Style:
Err-090
Width Between Flats:
Between 0.1270 inches and 0.1295 inches
Shank Diameter:
Between 0.3115 inches and 0.3120 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.6287 inches and 0.6335 inches
Lubrication:
Solid film or dry film and cetyl alcohol, specification 305, hi-shear corp
End Application:
W/s: aircraft, hornet f/a-18
Grip Length:
Between 0.745 inches and 0.755 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Thread Size:
0.312 inches
Shear Strength:
125000 single pounds per square inch
Countersink Angle:
100.0 degrees
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response

Unjf

**Thread Series Designator:** 

## NSN 5320-01-332-7353

Pin-rivet - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0