

View Online at <https://aerobasegroup.com/nsn/5320-01-332-7858>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.552 inches and 1.572 inches

Head Style:

Err-090

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3115 inches and 0.3120 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.6287 inches and 0.6335 inches

Lubrication:

Solid film or dry film and cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 1.057 inches and 1.067 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Thread Size:

0.312 inches

Shear Strength:

125000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0