NSN 5320-01-332-8024

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-332-8024

Head Style:	
-------------	--

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.1970 inches and 0.1990 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

0.375 inches

Expansion Device:

Threaded stem

Lubrication:

Dry film or cetyl alcohol or paraffin wax

Grip Length:

Between 0.470 inches and 0.531 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Complete top surface of head shall be powder blasted to produce a surface finish of ra 50/80 micro inches after all manufacturing operations

Material:

Titanium alloy uns r56400 stem

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

Surface Treatment:

Passivate sleeve

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0