

View Online at <https://aerobasegroup.com/nsn/5320-01-333-4572>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.875 inches and 1.895 inches

Head Style:

Err-090

Head Height:

Between 0.170 inches and 0.180 inches

Width Between Flats:

Between 0.1895 inches and 0.1930 inches

Shank Diameter:

Between 0.4365 inches and 0.4370 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.641 inches and 0.676 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 1.245 inches and 1.260 inches

Thread Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

201000 pounds per square inch

Thread Size:

0.438 inches

Shear Strength:

117000 single pounds per square inch

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Spec, 258, cagec 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0