NSN 5320-01-333-4577

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-333-4577 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.659 inches and 0.679 inches **Head Style:** Err-090 **Head Height:** Between 0.055 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.295 inches and 0.315 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.339 inches and 0.349 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches Material: Aluminum alloy 7075 **Material Specification:** Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-333-4577

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.