## NSN 5320-01-333-6480

Blind Rivet - Page 1 of 1

Fiig: A040a0



View Online at https://aerobasegroup.com/nsn/5320-01-333-6480 **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.1970 inches and 0.1990 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Head Major Diameter:** 0.375 inches **Expansion Device:** Threaded stem Lubrication: Dry film or cetyl alcohol or paraffin wax **Grip Length:** Between 0.157 inches and 0.219 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Complete top surface of head shall be powder blasted to produce a surface finish of ra 50/80 micro inches after all manufacturing operations Material: Titanium alloy uns r56400 stem **Material Specification:** Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve **Surface Treatment:** Passivate sleeve **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response sleeve Shelf Life: N/a **Unit Of Measure: Demilitarization:** No