

View Online at <https://aerobasegroup.com/nsn/5320-01-333-8116>

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.1965 inches and 0.1985 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

Between 0.378 inches and 0.385 inches

Expansion Device:

Threaded stem

Lubrication:

Dry film or cetyl alcohol or paraffin wax

Grip Length:

Between 0.350 inches and 0.400 inches

Features Provided:

Drive nut

Min. Tensile Strength (psi):

95000 pounds per square inch

Countersink Angle:

Between 129.0 degrees and 131.0 degrees

Special Features:

Acetal per I-p-392, insert; mild steel, color brown, drivenut; 175ksi ftu , screw; locking feature consists of 3 indentations located 120 degrees apart on the periphery of the nut component

Heat Treatment:

Annealed sleeve

Material:

Titanium alloy uns r56400 nut

Material Specification:

Mil-t-9047 military specification single material response nut or ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut

Surface Treatment:

Phosphate nut

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-t-9047 spec.