## NSN 5320-01-333-8875

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-333-8875 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.789 inches **Head Style:** Err-090 **Head Height:** Between 0.068 inches and 0.078 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3110 inches and 0.3120 inches **Shank Style: Head Major Diameter:** Between 0.475 inches and 0.505 inches Lubrication: Cetyl alcohol **Grip Length:** 1.375 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Shear Strength:** 108000 single pounds per square inch **Special Features:** 32 micro inches on shank Material: Steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** 

Shelf Life: N/a

Unjf

## NSN 5320-01-333-8875

Pin-rivet - Page 2 of 2



ι	Jn	it	Of	Measure:	•

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.