# NSN 5320-01-333-9943

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-333-9943

# Head Style:

Hexagon

**Head Height:** 

0.113 inches

# Shank Diameter:

Between 0.213 inches and 0.215 inches

# Shank Style:

Threaded self-plugging shank w/sleeve

#### **Expansion Device:**

Threaded stem

Grip Length:

Between 0.459 inches and 0.499 inches

## Width Across Flats:

Between 0.332 inches and 0.346 inches

#### Hardness Rating:

39.0 rockwell c bolt and 43.0 rockwell c bolt

#### Material:

Steel comp 304 sleeve or steel comp 303 sleeve or steel comp 303f sleeve

# Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams5639 assn standard 1st material response sleeve or astm a582 assn

standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

### Surface Treatment:

Cadmium sleeve and chromate sleeve and passivate sleeve

## Surface Treatment Specification:

Qq-p-416, type 2, I 2 federal specification single treatment response bolt

#### **Specification Data:**

80205-nas1755 professional/industrial association standard

Shelf Life:

N/a

#### Unit Of Measure:

---

#### **Demilitarization:**

No

# Fiig:

A040a0

#### Mil-std (military Standard):

Mil-s-5626 spec.