NSN 5320-01-333-9962

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-333-9962



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.253 inches and 1.273 inches

Head Style:

Err-090

Head Height:

Between 0.055 inches and 0.074 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.933 inches and 0.943 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Special Features:

Dye color natural

Heat Treatment:

T-6 solution heat treated

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5320-01-333-9962

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.

