## NSN 5320-01-333-9979

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-333-9979



## Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.146 inches and 1.171 inches

## Head Style:

Err-090

## Head Height:

Between 0.082 inches and 0.094 inches

## Shank Diameter:

0.4068 inches

### Shank Style:

Pin-rivet, tapered, threaded

### Head Major Diameter:

Between 0.582 inches and 0.596 inches

#### Tip Diameter:

0.3932 inches

## Lubrication:

Cetyl alcohol and dry film

### Grip Length:

Between 0.740 inches and 0.755 inches

## Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

220000 pounds per square inch

### **Thread Size:**

0.375 inches

### Shear Strength:

125000 single pounds per square inch

### Material:

Steel comp xm-13

### **Material Specification:**

Ams 5629 assn standard single material response

### Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-333-9979

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

