

View Online at <https://aerobasegroup.com/nsn/5320-01-334-3699>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.660 inches and 1.680 inches

Head Style:

Err-090

Head Height:

Between 0.150 inches and 0.160 inches

Width Between Flats:

Between 0.1582 inches and 0.1617 inches

Shank Diameter:

Between 0.3740 inches and 0.3745 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.565 inches and 0.600 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 1.120 inches and 1.135 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

201000 pounds per square inch

Thread Size:

0.375 inches

Shear Strength:

117000 single pounds per square inch

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Spec, 258, cagec 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0