## NSN 5320-01-334-4757

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-334-4757 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.193 inches and 1.218 inches **Head Style:** Err-090 **Head Height:** Between 0.082 inches and 0.094 inches **Shank Diameter:** 0.4224 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.605 inches and 0.619 inches Tip Diameter: 0.4089 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** Between 0.740 inches and 0.755 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 125000 single pounds per square inch Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** 

Unjf Shelf Life:

N/a

## NSN 5320-01-334-4757

Pin-rivet - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A528u0