# NSN 5320-01-334-7972

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-334-7972

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.1970 inches and 0.1990 inches

## Shank Style:

Threaded self-plugging shank w/sleeve

# Head Major Diameter:

0.342 inches

#### **Expansion Device:**

Threaded stem

#### Lubrication:

Paraffin wax or cetyl alcohol

## Grip Length:

Between 0.282 inches and 0.344 inches

## **Features Provided:**

Drive nut

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

## **Special Features:**

Drive nut color light gray. Complete top surface of head of nut shall be powder blasted to produce a surface finish of ra 50/80 micro inches

after all manufacturing operations

## Material:

Titanium alloy uns r56400 nut

## **Material Specification:**

Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut

#### Surface Treatment:

Passivate sleeve

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response sleeve

## Shelf Life:

N/a

#### Unit Of Measure:

---

#### **Demilitarization:**

No

## Fiig:

A040a0