NSN 5320-01-334-9733

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-334-9733
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.121 inches and 1.146 inches
Head Style:
Flush countersunk
Shank Diameter:
0.3403 inches
Shank Style:
Pin-rivet, tapered, threaded
Head Major Diameter:
0.508 inches
Tip Diameter:
0.3280 inches
Lubrication:
Dry film and cetyl alcohol
Grip Length:
Between 0.740 inches and 0.755 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Thread Size:
0.312 inches
Shear Strength:
125000 single pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
8-32unjc-3b thread size, 0.390 in. Lg along the longitudinal axis from the head end. 0.120 in. Slot lg. 0.060 in. Slot w located 0.330 in. From
top of head to center of slot
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:

Unjf

NSN 5320-01-334-9733

Pin-rivet - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0