# NSN 5320-01-335-3414

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-335-3414



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 1.193 inches and 1.218 inches

## Head Style:

Err-090

#### Head Height:

Between 0.120 inches and 0.132 inches

Shank Diameter:

0.4563 inches

Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.669 inches and 0.685 inches

**Tip Diameter:** 

0.4428 inches

Lubrication:

Dry film and cetyl alcohol

Grip Length:

Between 0.740 inches and 0.755 inches

Thready Qty Per Inch (tpi):

20

#### Min. Tensile Strength (psi):

220000 pounds per square inch

**Thread Size:** 

0.437 inches

Shear Strength:

125000 single pounds per square inch

Material:

Steel comp xm-13

#### **Material Specification:**

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

#### Shelf Life:

N/a

# NSN 5320-01-335-3414

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

