NSN 5320-01-335-3416

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-335-3416 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.4975 inches and 0.5175 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.104 inches and 0.119 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.357 inches and 0.377 inches Lubrication: Solid film and cetyl alcohol **End Application:** C17 **Grip Length:** Between 0.1825 inches and 0.1925 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 5380 double pounds per square inch **Product Name:** Pin-rivet, threaded Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 assn standard single material response or ams 4928 assn standard single material response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5320-01-335-3416

Pin-rivet - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A528u0