

View Online at <https://aerobasegroup.com/nsn/5320-01-335-3418>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.697 inches and 0.717 inches

Head Style:

Err-090

Head Height:

Between 0.080 inches and 0.090 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.307 inches and 0.317 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

210000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

125000 single pounds per square inch

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0