

View Online at <https://aerobasegroup.com/nsn/5320-01-335-4687>

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.1965 inches and 0.1985 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

Between 0.378 inches and 0.385 inches

**Expansion Device:**

Threaded stem

**Lubrication:**

Dry film or cetyl alcohol or paraffin wax

**Grip Length:**

Between 0.250 inches and 0.300 inches

**Features Provided:**

Drive nut

**Min. Tensile Strength (psi):**

95000 pounds per square inch

**Countersink Angle:**

Between 129.0 degrees and 131.0 degrees

**Special Features:**

Acetal per I-p-392, insert; mild steel, color brown, drivenut; 175 ksi ftu , screw; locking feature consists of 3 indentations located 120 degrees apart on the periphery of the nut component

**Heat Treatment:**

Annealed sleeve

**Material:**

Titanium alloy uns r56400 nut

**Material Specification:**

Mil-t-9047 military specification single material response nut or ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut

**Surface Treatment:**

Phosphate nut

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-t-9047 spec.