## NSN 5320-01-336-0084

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-336-0084

Between 1.010 inches and 1.210 inches Head Style: Flush countersunk Shank Diameter: Between 0.1630 inches and 0.1635 inches Shank Style: Pin-rivet, multiple grooved Head Major Diameter: 0.332 inches Lubrication: Cetyl alcohol Grip Length: Between 0.251 inches and 0.312 inches Shear Strength: 95000 single pounds per square inch Countersink Angle: Between 129.0 degrees and 131.0 degrees Special Features: Bare parts only. Complete top surface of head shall be powder blasted to produce a surface finish of 50/80 microinches after all manufacturing operations and prior to cetyl alcohol lubrication Material: Titanium alloy uns r56400 Material Specification: Ams 4967 assn standard single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A52800	Fastener Length:
Flush countersunk Shank Diameter: Between 0.1630 inches and 0.1635 inches Shank Style: Pin-rivet, multiple grooved Head Major Diameter: 0.332 inches Bubrication: Cetyl alcohol Grip Length: Between 0.251 inches and 0.312 inches Shear Strength: 95000 single pounds per square inch Countersink Angle: Between 12.9.0 degrees and 131.0 degrees Special Features: Bare parts only. Complete top surface of head shall be powder blasted to produce a surface finish of 50/80 microinches after all manufacturing operations and prior to cetyl alcohol lubrication Material: Titanium alloy uns r56400 Material Specification: Ams 4967 assn standard single material response Shelf Life: V/a Unit Of Measure: Demilitarization: No Filg:	Between 1.010 inches and 1.210 inches
Shank Diameter: Between 0.1630 inches and 0.1635 inches Shank Style: Pin-rivet, multiple grooved Head Major Diameter: 0.332 inches Lubrication: Cetyl alcohol Grip Length: Between 0.251 inches and 0.312 inches Shear Strength: 95000 single pounds per square inch Countersink Angle: Between 129.0 degrees and 131.0 degrees Special Features: Bare parts only. Complete top surface of head shall be powder blasted to produce a surface finish of 50/80 microinches after all manufacturing operations and prior to cetyl alcohol lubrication Material: Titanium alloy uns r56400 Material Specification: Ams 4967 assn standard single material response Shelf Life: Na Unit Of Measure: Demilitarization: No Fiig:	Head Style:
Between 0.1630 inches and 0.1635 inches  Shank Style:  Pin-rivet, multiple grooved  Head Major Diameter: 0.332 inches  Lubrication: Cetyl alcohol Grip Length: Between 0.251 inches and 0.312 inches Shear Strength: 95000 single pounds per square inch Countersink Angle: Between 129.0 degrees and 131.0 degrees Special Features: Bare parts only. Complete top surface of head shall be powder blasted to produce a surface finish of 50/80 microinches after all manufacturing operations and prior to cetyl alcohol lubrication Material: Tittanium alloy uns r56400 Material Specification: Ams 4967 assn standard single material response Shelf Life: Na Unit Of Measure: Demilitarization: No Filg:	Flush countersunk
Shank Style: Pin-rivet, multiple grooved Head Major Diameter: 0.332 inches Lubrication: Cetyl alcohol Grip Length: Between 0.251 inches and 0.312 inches Shear Strength: 95000 single pounds per square inch Countersink Angle: Between 129.0 degrees and 131.0 degrees Special Features: Bare parts only. Complete top surface of head shall be powder blasted to produce a surface finish of 50/80 microinches after all manufacturing operations and prior to cetyl alcohol lubrication Material: Titanium alloy uns r56400 Material Specification: Arns 4967 assn standard single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Shank Diameter:
Pin-rivet, multiple grooved  Head Major Diameter:  0.332 inches  Lubrication: Cetyl alcohol  Grip Length: Between 0.251 inches and 0.312 inches  Shear Strength: 95000 single pounds per square inch  Countersink Angle: Between 129.0 degrees and 131.0 degrees  Special Features: Bare parts only. Complete top surface of head shall be powder blasted to produce a surface finish of 50/80 microinches after all manufacturing operations and prior to cetyl alcohol lubrication  Material: Titanium alloy uns r56400  Material Specification: Ams 4967 assn standard single material response  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No Fiig:	Between 0.1630 inches and 0.1635 inches
Head Major Diameter:  0.332 inches  Lubrication: Cetyl alcohol Grip Length: Between 0.251 inches and 0.312 inches Shear Strength: 95000 single pounds per square inch Countersink Angle: Between 129.0 degrees and 131.0 degrees Special Features: Bare parts only. Complete top surface of head shall be powder blasted to produce a surface finish of 50/80 microinches after all manufacturing operations and prior to cetyl alcohol lubrication Material: Titanium alloy uns r56400 Material Specification: Ams 4967 assn standard single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Shank Style:
0.332 inches Lubrication: Cetyl alcohol Grip Length: Between 0.251 inches and 0.312 inches Shear Strength: 95000 single pounds per square inch Countersink Angle: Between 129.0 degrees and 131.0 degrees Special Features: Bare parts only. Complete top surface of head shall be powder blasted to produce a surface finish of 50/80 microinches after all manufacturing operations and prior to cetyl alcohol lubrication Material: Titanium alloy uns r56400 Material Specification: Ams 4967 assn standard single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Pin-rivet, multiple grooved
Lubrication: Cetyl alcohol Grip Length: Between 0.251 inches and 0.312 inches Shear Strength: 95000 single pounds per square inch Countersink Angle: Between 129.0 degrees and 131.0 degrees Special Features: Bare parts only. Complete top surface of head shall be powder blasted to produce a surface finish of 50/80 microinches after all manufacturing operations and prior to cetyl alcohol lubrication Material: Titanium alloy uns r56400 Material Specification: Ams 4967 assn standard single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Head Major Diameter:
Cetyl alcohol  Grip Length:  Between 0.251 inches and 0.312 inches Shear Strength:  95000 single pounds per square inch  Countersink Angle:  Between 129.0 degrees and 131.0 degrees  Special Features:  Bare parts only. Complete top surface of head shall be powder blasted to produce a surface finish of 50/80 microinches after all manufacturing operations and prior to cetyl alcohol lubrication  Material:  Titanium alloy uns r56400  Material Specification:  Arms 4967 assn standard single material response  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	0.332 inches
Grip Length:  Between 0.251 inches and 0.312 inches  Shear Strength:  95000 single pounds per square inch  Countersink Angle:  Between 129.0 degrees and 131.0 degrees  Special Features:  Bare parts only. Complete top surface of head shall be powder blasted to produce a surface finish of 50/80 microinches after all manufacturing operations and prior to cetyl alcohol lubrication  Material:  Titanium alloy uns r56400  Material Specification:  Ams 4967 assn standard single material response  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Lubrication:
Between 0.251 inches and 0.312 inches  Shear Strength:  95000 single pounds per square inch  Countersink Angle:  Between 129.0 degrees and 131.0 degrees  Special Features:  Bare parts only. Complete top surface of head shall be powder blasted to produce a surface finish of 50/80 microinches after all manufacturing operations and prior to cetyl alcohol lubrication  Material:  Titanium alloy uns r56400  Material Specification:  Ams 4967 assn standard single material response  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Cetyl alcohol
Shear Strength: 95000 single pounds per square inch Countersink Angle: Between 129.0 degrees and 131.0 degrees Special Features: Bare parts only. Complete top surface of head shall be powder blasted to produce a surface finish of 50/80 microinches after all manufacturing operations and prior to cetyl alcohol lubrication Material: Titanium alloy uns r56400 Material Specification: Ams 4967 assn standard single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Grip Length:
95000 single pounds per square inch  Countersink Angle:  Between 129.0 degrees and 131.0 degrees  Special Features:  Bare parts only. Complete top surface of head shall be powder blasted to produce a surface finish of 50/80 microinches after all manufacturing operations and prior to cetyl alcohol lubrication  Material:  Titanium alloy uns r56400  Material Specification:  Ams 4967 assn standard single material response  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Between 0.251 inches and 0.312 inches
Countersink Angle: Between 129.0 degrees and 131.0 degrees  Special Features: Bare parts only. Complete top surface of head shall be powder blasted to produce a surface finish of 50/80 microinches after all manufacturing operations and prior to cetyl alcohol lubrication  Material: Titanium alloy uns r56400  Material Specification: Ams 4967 assn standard single material response  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Shear Strength:
Between 129.0 degrees and 131.0 degrees  Special Features:  Bare parts only. Complete top surface of head shall be powder blasted to produce a surface finish of 50/80 microinches after all manufacturing operations and prior to cetyl alcohol lubrication  Material:  Titanium alloy uns r56400  Material Specification:  Ams 4967 assn standard single material response  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	95000 single pounds per square inch
Special Features:  Bare parts only. Complete top surface of head shall be powder blasted to produce a surface finish of 50/80 microinches after all manufacturing operations and prior to cetyl alcohol lubrication  Material:  Titanium alloy uns r56400  Material Specification:  Ams 4967 assn standard single material response  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Countersink Angle:
Bare parts only. Complete top surface of head shall be powder blasted to produce a surface finish of 50/80 microinches after all manufacturing operations and prior to cetyl alcohol lubrication  Material:  Titanium alloy uns r56400  Material Specification:  Ams 4967 assn standard single material response  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Between 129.0 degrees and 131.0 degrees
manufacturing operations and prior to cetyl alcohol lubrication  Material: Titanium alloy uns r56400  Material Specification: Ams 4967 assn standard single material response  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Special Features:
Material: Titanium alloy uns r56400  Material Specification: Ams 4967 assn standard single material response  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Bare parts only. Complete top surface of head shall be powder blasted to produce a surface finish of 50/80 microinches after all
Titanium alloy uns r56400  Material Specification: Ams 4967 assn standard single material response  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fiig:	manufacturing operations and prior to cetyl alcohol lubrication
Material Specification: Ams 4967 assn standard single material response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Ams 4967 assn standard single material response  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Titanium alloy uns r56400
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material Specification:
N/a Unit Of Measure: Demilitarization: No Fiig:	Ams 4967 assn standard single material response
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A528u0	Fiig:
	A528u0