NSN 5320-01-336-1339

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-336-1339

Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Blue
Fastener Length:
Between 0.628 inches and 0.648 inches
Head Style:
Err-090
Head Height:
Between 0.064 inches and 0.074 inches
Width Between Flats:
Between 0.079 inches and 0.081 inches
Shank Diameter:
Between 0.220 inches and 0.221 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.357 inches and 0.377 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 0.302 inches and 0.322 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.190 inches
Shear Strength:
5380 double pounds per square inch
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Hi-shear specification 306, type 1 blue mfr ref single treatment response
Thread Series Designator:
Unif

Unjt

NSN 5320-01-336-1339

Pin-rivet - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0