

View Online at <https://aerobasegroup.com/nsn/5320-01-336-4638>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.407 inches and 1.427 inches

Head Style:

Err-090

Head Height:

Between 0.045 inches and 0.055 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.2016 inches and 0.2026 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

Grip Length:

Between 1.057 inches and 1.067 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Special Features:

Hi-kote 1 per hi-shear spec. 294 and cetyl alcohol lube per hi-shear spec. 305

Material:

Steel

Material Specification:

Mil-s-5000 military specification single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, tyii, cl3 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

73197-hl56-6-17 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.