NSN 5320-01-337-1029

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-337-1029 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.052 inches and 1.072 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** 0.1465 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.6335 inches Lubrication: Solid film **Grip Length:** Between 0.557 inches and 0.567 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 210000 pounds per square inch Hardness Rating: 44.0 rockwell c and 50.0 rockwell c **Thread Size:** 0.312 inches **Countersink Angle:** 100.0 degrees **Special Features:** 0.138-32unjc-3b, threaded concentric hole along the longitudinal centerline of head end 0.300 in. Min. 0.345 in. Maximum dp. 0.120 in. Slot lg. 0.060 in. W located 0.300 in. From to p of head to beginning of slot Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response

N/a

Unjf

Shelf Life:

Thread Series Designator:

NSN 5320-01-337-1029

Pin-rivet - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A528u0