## NSN 5320-01-337-6707

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-337-6707

## Thread Class:

3b

#### **Thread Direction:**

Right-hand

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.387 inches and 0.390 inches

#### Shank Style:

Blind rivet, nut and bolt (assembly)

## Head Major Diameter:

0.450 inches

#### **Expansion Device:**

Threaded mandrel

#### Lubrication:

Solid film

## Grip Length:

0.625 inches

## Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

## Shear Strength:

125000 single pounds per square inch

## **Countersink Angle:**

Between 98.0 degrees and 102.0 degrees

## **Special Features:**

Furnished without bolt

## Heat Treatment:

Annealed sleeve

## Material:

Steel comp 305 sleeve or steel comp 302 sleeve or steel sleeve

## Material Specification:

Qq-s-763 federal specification 1st material response sleeve or qq-s-763 federal specification 2nd material response sleeve or astm a493 assn standard 3rd material response sleeve

## Thread Series Designator:

Unjf

Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5320-01-337-6707

Blind Rivet - Page 2 of 2

**Fiig:** A040a0

