## NSN 5320-01-337-6724

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-337-6724



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 1.030 inches and 1.050 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.045 inches and 0.055 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.295 inches and 0.315 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

Between 0.745 inches and 0.755 inches

#### Thready Qty Per Inch (tpi):

32

#### **Thread Size:**

0.190 inches

#### Shear Strength:

95000 single pounds per square inch

#### **Special Features:**

Color code orange on thread end

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum

#### Surface Treatment Specification:

Hi kote 1, cagec 73197 mfr ref single treatment response

### Thread Series Designator:

Unjf

#### Shelf Life:

N/a

# NSN 5320-01-337-6724

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

