NSN 5320-01-337-7109

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-337-7109



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.677 inches and 1.697 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3115 inches and 0.3120 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.6287 inches and 0.6335 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 1.182 inches and 1.192 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.312 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Phosphate flouride treatment with color red on thread end

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-337-7109

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

