

View Online at <https://aerobasegroup.com/nsn/5320-01-338-1021>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.072 inches and 2.092 inches

Head Style:

Err-090

Head Height:

Between 0.112 inches and 0.127 inches

Width Between Flats:

Between 0.2520 inches and 0.2555 inches

Shank Diameter:

Between 0.5610 inches and 0.5615 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.829 inches and 0.864 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 1.302 inches and 1.322 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.562 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

Color code red on thread end. Phosphatate fluoride surface treatment

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0