

View Online at <https://aerobasegroup.com/nsn/5320-01-338-1023>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.347 inches and 1.367 inches

Head Style:

Err-090

Head Height:

Between 0.078 inches and 0.088 inches

Width Between Flats:

Between 0.1582 inches and 0.1617 inches

Shank Diameter:

Between 0.3735 inches and 0.3745 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.565 inches and 0.600 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.807 inches and 0.817 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.375 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

Color code black on thread end

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi kote 1, cagc 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0