NSN 5320-01-338-4194

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-338-4194 **Fastener Length:** 1.737 inches **Head Style:** Universal **Head Height:** Between 0.107 inches and 0.117 inches **Shank Diameter:** Between 0.252 inches and 0.256 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** Between 0.490 inches and 0.510 inches **Expansion Device:** Serrated stem-type w **Grip Length:** Between 0.126 inches and 0.187 inches Min. Tensile Strength (psi): 1125000 pounds per square inch **Shear Strength:** 2615 single pounds per square inch Material: Iron alloy 660 collaraluminum alloy 5056 sleevesteel comp 8740 stem **Material Specification:** Ams 5731 assn standard single material response collargq-a-430 federal specification single material response sleeveams 6322 assn standard single material response stem **Surface Treatment:** Chromate sleevecadmium stem and chromate stem **Surface Treatment Specification:** Mil-c-5541 military specification single treatment response sleeveqq-p-416, type 2, cl 2 federal specification single treatment response stem Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-c-5541 spec.