

View Online at <https://aerobasegroup.com/nsn/5320-01-338-4194>

**Fastener Length:**

1.737 inches

**Head Style:**

Universal

**Head Height:**

Between 0.107 inches and 0.117 inches

**Shank Diameter:**

Between 0.252 inches and 0.256 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.490 inches and 0.510 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.126 inches and 0.187 inches

**Min. Tensile Strength (psi):**

1125000 pounds per square inch

**Shear Strength:**

2615 single pounds per square inch

**Material:**

Iron alloy 660 collaraluminum alloy 5056 sleevesteel comp 8740 stem

**Material Specification:**

Ams 5731 assn standard single material response collarqq-a-430 federal specification single material response sleeveams 6322 assn standard single material response stem

**Surface Treatment:**

Chromate sleevecadmium stem and chromate stem

**Surface Treatment Specification:**

Mil-c-5541 military specification single treatment response sleeveqq-p-416, type 2, cl 2 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-c-5541 spec.