## NSN 5320-01-338-4230

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-338-4230

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.672 inches and 1.692 inches
Head Style:
Err-090
Head Height:
Between 0.068 inches and 0.078 inches
Width Between Flats:
Between 0.1270 inches and 0.1295 inches
Shank Diameter:
Between 0.3110 inches and 0.3120 inches
Shank Style:
Head Major Diameter:
Between 0.475 inches and 0.505 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 1.182 inches and 1.192 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.312 inches
Shear Strength:
95000 single pounds per square inch
Special Features:
Idenitfy with color code black on thread end
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Hi kote 1, cagec 73197 mfr ref single treatment response
Thread Series Designator:

Unjf

## NSN 5320-01-338-4230

Pin-rivet - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0