## NSN 5320-01-338-4232

Pin-rivet - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5320-01-338-4232 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.497 inches and 1.517 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style: Head Major Diameter:** Between 0.3898 inches and 0.3948 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.177 inches and 1.197 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Identify with color code black on thread end Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Hi-kote 1, spec. 294, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

## NSN 5320-01-338-4232

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0